



## MIXERS OPTIMIX-3P | ESPECIFICACIONES TÉCNICAS

**STAAL**

Modelos	2.0	3.0
LARGOR (M)	1,24	1,24
ALTURA (M)	1,23	1,23
Ancho (M)	2,72	2,72
Comando hidráulico (Req. tractor)	Si	Si
Tractor HP	65	65
TDF ~	540	540



## MIXERS OPTIMIX-V | ESPECIFICACIONES TÉCNICAS

**STAAL**

Modelos	4.0	6.0	8.0	10.0	12.0
Capacidad en M <sup>3</sup>	4M <sup>3</sup> (1,6)	6M <sup>3</sup> (2,4)	8M <sup>3</sup> (3,2)	10M <sup>3</sup> (4,0)	12M <sup>3</sup> (4,8)
Largor (M)	5,2	5,2	6,1	6,35	6,35
Altura (M)	2,8	3,06	3	3,2	3,45
Ancho (M)	2,27	2,27	2,62	2,62	2,62
Rotación TDF (RPM)	540	540	540	540	540
Tiempo de mezcla (Min)	5	5	5	7	7
Descarga cinta (Gravedad)	Cinta PVC	Cinta PVC	Cinta PVC	Cinta PVC	Cinta PVC
Peso Neto (TON ≈)	1,8	2,2	3,2	3,3	3,4
Pala trasera (Opcional)	Si	Si	Si	Si	Si
Sin fin cónico vertical (Un)	1	1	1	1	1



## MIXERS OPTIMIX-VD | ESPECIFICACIONES TÉCNICAS

**STAAL**

Modelos	14.0	16.0	18.0	20.0
Capacidad en M <sup>3</sup>	14M <sup>3</sup> (5,6)	16M <sup>3</sup> (6,4)	18M <sup>3</sup> (7,2)	20M <sup>3</sup> (8,0)
Largor (M)	6,4	6,6	6,6	7,1
Altura (M)	2,88	3,1	3,2	3,31
Ancho (M)	2,39	2,62	2,62	2,75
Rotación TDF (RPM)	540	540	540	540
Tiempo de mezcla (Min)	10	10	10	10
Descarga cinta (Gravedad)	Cinta PVC	Cinta PVC	Cinta PVC	Cinta PVC
Peso Neto (TON ≅)	5,2	5,2	5,4	7,1
Pala trasera (Opcional)	No	No	No	No
Sin fin cónico vertical (Un)	2	2	2	2